



DETAIL A



Soft seat
with metal core

DETAIL B



Abmessungen / Dimensions*

DN	INCH	A	B	C	D	E	ØF	G	H	I
50	2"	113	159,5	183	131	100	80	40	96	1/4"gas
65	2 1/2"	113	168,5	198	155	100	80	40	96	1/4"gas
80	3"	117,5	184,5	214,5	168	118	100	50	98,5	3/8"gas
100	4"	132,5	204,5	235	189	118	100	50	98,5	3/8"gas
125	5"	151	235,5	263	182,5	144	125	50	98,5	3/8"gas
150	6"	167	264	302	211	144	125	60	98,5	3/8"gas
200	8"	196	322,5	340,5	262	180	160	60	124	3/8"gas
250	10"	228	374,5	394	316	180	160	70	124	3/8"gas
300	12"	274	430	460	375	215	200	70	136	1/2"gas
350	14"	308	480	510	423	215	200	96	136	1/2"gas
400	16"	362	556	579	476	280	250	100	175	1/2"gas
500	20"	473	666,5	675	590	280	250	110	189	1/2"gas

Werkstoffe / Materials*

	GG25 type	Stainless steel type
1 Gehäuse / Body	GG25	CF8M/ 1.4408
2 Platte / Gate	AISI 304 / 1.4301	AISI 316L
3 Spindel / Stem	AISI 303 / 1.4305	
4 Sitz / Seat	NBR / EPDM / Viton / PTFE / Butyl / Metal	
5 Packung / Packing	3-lagig gewachste Baumwolle / 3-layered greased cotton	
6 Dichtung / Sealing	NBR / EPDM / Viton / PTFE	

Druckstufen / Pressure

DN50 - DN250:	10 bar
DN300:	6 bar
DN350-DN400:	5 bar
DN450-DN500:	4 bar

Farbe / Colour*

 RAL 5015

Flansche gebohrt nach / Flanges drilled according to
ANSI B16.5 (class 150) and DIN 2501: ISO PN10

*Andere Maße, Werkstoffe und Farben auf Anfrage / Other dimensions, materials and colours on request



Design and materials can be changed without notice. Errors and omissions excepted.

FB100 - pneumatic double acting

copyright © by
FERGO® Armaturen GmbH

Blindeisenweg 31
D-41468 Neuss

Tel.: +49(0) 2131 - 15 39 28-0
Fax: +49(0) 2131 - 15 39 28-99

Web: www.fergo.biz
E-Mail: info@fergo.biz

fergo®