



Dimensions*

DN	INCH	A	B	C	D	E	X
50	2"	40	92	220	240	630	9
65	2 1/2"	40	92	260	270	655	9
80	3"	50	92	303	295	680	9
100	4"	50	92	360	335	720	9
125	5"	50	102	428	370	805	9
150	6"	60	102	493	418	855	9
200	8"	60	119	632	522	1050	9
250	10"	70	119	767	625	1250	9
300	12"	70	119	897	725	1350	12
350	14"	96	192	1042	845	1510	12
400	16"	100	192	1167	945	1615	12
450	18"	106	192	1297	1045	1870	12
500	20"	110	192	1455	1148	1986	12
600	24"	110	290	1705	1360	2115	12

Materials*

	GG25 type	Stainless steel type
1 Body	GG25	1.4408/CF8M
2 Packing gland	Aluminium	1.4408/SS316
3 Gate	1.4301/SS304	1.4408/SS316
4 Support plates	Steel	Steel
5 Motor		
6 Grower washer	Steel	Steel
7 Bolts	Steel	Stainless steel
8 Studs	Steel	Stainless steel
9 Nuts	Steel	Stainless steel
10 Spindle	1.4301/SS304	1.4301/SS304
11 Manoeuvring support	Steel	Stainless steel
12 Tube	Steel	Stainless steel
13 Cover	Autobloc	Autobloc
14 Seat	EPDM / NBR / Viton / Silicon / Flucast ABP / PTFE	
15 Ring	1.4408/SS316	1.4408/SS316
16 Packing	Synt. + PTFE / PTFE / Graphite / Ceramic fibre	
17 Toric joint	Nitrile	Nitrile
18 Studs	Steel	Stainless steel
19 Washer	Steel	Stainless steel
20 Nut	Steel	Stainless steel

Pressure

DN50 - DN250:	10 bar
DN300 - DN400:	6 bar
DN450:	5 bar
DN500 - DN600:	4 bar
DN700 - DN1200:	2 bar

Colour*

RAL 5015

Flanges drilled according to EN 1092-2, DIN 2501: ISO PN10 and ANSI B16.5 (class 150)

(for further informations please visit our download section on our website)

*Other dimensions / materials / colours on request