







DETAIL A



DETAIL B



Dimensions*

DN	INCH	A	B	C	D	E	X
200	8"	60	119	632	522	930	9
250	10"	70	119	767	625	1130	9
300	12"	70	119	897	725	1230	12
350	14"	96	192	1042	845	1502	12
400	16"	100	192	1167	945	1607	12
450	18"	106	192	1297	1045	1697	12
500	20"	110	192	1455	1148	1813	12
600	24"	110	290	1705	1360	2148	12

Materials*

	GG25 type	Stainless steel type
1 Body	GG25	1.4408/CF8M
2 Packing gland	Aluminium	1.4408/SS316
3 Gate	1.4301/SS304	1.4408/SS316
4 Support plates	Steel	Steel
5 Bolts	Steel	Aluminium
6 Studs	Steel	Aluminium
7 Nuts	Steel	Stainless steel
8 Spindle	1.4301/SS304	1.4301/SS304
9 Grower washer	Steel	Stainless steel
10 Manoeuvring support	Steel	Stainless steel
11 Reducer		
12 Handwheel	Steel	Stainless steel
13 Tube	Steel	Stainless steel
14 Cover	Plastic	Plastic
15 Seat	EPDM / NBR / Viton / Silicon / Flucast ABP / PTFE	
16 Ring	1.4408/SS316	1.4408/SS316
17 Packing	Synt. + PTFE / PTFE / Graphite / Ceramic fibre	
18 Toric joint	Nitrile	Nitrile
19 Studs	Steel	Stainless steel
20 Washer	Steel	Stainless steel
21 Nut	Steel	Stainless steel

Pressure

DN50 - DN250:	10 bar
DN300 - DN400:	6 bar
DN450:	5 bar
DN500 - DN600:	4 bar
DN700 - DN1200:	2 bar

Colour*

 RAL 5015

Flanges drilled according to EN 1092-2, DIN 2501: ISO PN10 and ANSI B16.5 (class 150)

(for further informations please visit our download section on our website)

*Other dimensions / materials / colours on request