







DETAIL A



DETAIL B



Dimensions*

DN	INCH	A	B	C	D	E	F	G
50	2"	40	92	220	244	150	300	395
65	2 1/2"	40	92	260	268	150	300	435
80	3"	50	92	303	296	150	300	458
100	4"	50	92	360	336	150	400	590
125	5"	50	102	428	370	150	400	725
150	6"	60	102	493	421	150	400	892
200	8"	60	119	632	527	323	600	1280
250	10"	70	119	767	628	323	600	1430
300	12"	70	119	897	728	323	600	1580

Materials*

	GG25 type	Stainless steel type
1 Body	GG25	1.4408/CF8M
2 Packing gland	Aluminium	1.4408/SS316
3 Gate	1.4301/SS304	1.4408/SS316
4 Support plates	Steel	Steel
5 Nuts	Steel	Stainless steel
6 Nuts	Steel	Stainless steel
7 Nuts	Steel	Stainless steel
8 Shaft	1.4301/SS304	1.4301/SS304
9 Washer	Steel	Stainless steel
10 Actuator nut	Bronze	Bronze
11 Bridge	Steel	Steel
12 Washer	Brass	Brass
13 Chainwheel	Steel	Steel
14 Screw	Steel	Steel
15 Lever	Plastic	Plastic
16 Seat	EPDM / NBR / Viton / Silicon / Flucast ABP / PTFE	
17 Sealing ring	1.4408/SS316	1.4408/SS316
18 Packing	Synt. + PTFE / PTFE / Graphite / Ceramic fibre	
19 Packing joint	EPDM / NBR / Viton / PTFE	
20 Gland studs	Steel	Stainless steel
21 Washer	Steel	Stainless steel
22 Nut	Steel	Stainless steel

Pressure

DN50 - DN250:	10 bar
DN300 - DN400:	6 bar
DN450:	5 bar
DN500 - DN600:	4 bar
DN700 - DN1200:	2 bar

Colour*

RAL 5015

Flanges drilled according to EN 1092-2, DIN 2501: ISO PN10 and ANSI B16.5 (class 150)

(for further informations please visit our download section on our website)

*Other dimensions / materials / colours on request