

SOLENOID VALVES

FERGO® Solenoid valves

The high quality and reliability of FERGO®'s solenoid valves guarantee a lifespan of over 12.000.000 operations.

Various surface treatments are suitable for every application. We also provide different threads for highest flexibility: BSP, PT or NPT.

The enormous versatility of FERGO®'s solenoid valves enable an exactly fitting quotation according to your specified demand.

Technical data

Pressure range:	1,5 to 8 bar
Temperature:	-20 to 70°C
Body diameter:	1/8" to 1/2"
Connection size:	1/8" to 1/2"
Voltages:	AC110 V, AC220 V, AC280 V, DC24 V, DC12 V, AC36 V, AC24 V, DC110 V, DC48 V und DC36 V
Body material:	Aluminium
Coil housing:	Aluminium
Connection housing:	Fibre
O-Rings:	NBR
Sealing:	NBR
Coil spring:	Stainless steel

- » Over 12.000.000 operations guaranteed
- » Absolute flexibility due to enormous variety
- » Display of voltage activity via red LED in connected housing



3/2 Way, Solenoid valve, Namur



5/2 Way, Solenoid valve, Namur



5/2 Way, Solenoid valve, Namur



5/2 Way, Solenoid valve (not Namur)



Display of voltage activity via red LED

fergo®