



- D** • Anschluss ISO 228/1
 • Gehäuse: Messing, verchromt
 • Scheibe: Messing, verchromt
 • Min. Betriebsdruck: 0,03 bar
 • Max. Betriebsdruck: 18 bar/25 bar
 • Max. Temperatur: 90°C

- E** • Threaded ends acc. to ISO 228/1
 • Body: Brass, chromed
 • Disc: Brass, chromed
 • Min. working pressure: 0,03 bar
 • Max. working pressure: 18 bar/25 bar
 • Max. Temperature: 90°C



RV104

Maße / Dimensions [mm]

| Inch | PN | R | P | A | D | Gewicht/weight[g] |
|--------|----|--------|----|-----|----|-------------------|
| 1/2" | 25 | 1/2" | 15 | 78 | 28 | 90 |
| 3/4" | 25 | 3/4" | 20 | 91 | 35 | 150 |
| 1" | 25 | 1" | 25 | 97 | 42 | 235 |
| 1 1/4" | 18 | 1 1/4" | 32 | 113 | 52 | 340 |
| 1 1/2" | 18 | 1 1/2" | 40 | 128 | 63 | 510 |
| 2" | 18 | 2" | 50 | 150 | 78 | 760 |

Materials

| Nr. | Bauteil/Part | Material |
|-----|------------------------------|----------------------------------|
| 1 | Gehäuse/Body | Messing, verchromt/Brass,chromed |
| 2 | Sitz/Seat | NBR |
| 3 | Feder/Spring | AISI 316 |
| 4 | Federanschlag/Stopper spring | Messing/Brass |
| 5 | Sieb/Filter | AISI 304 |